(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 6 May 2005 (06.05.2005)

PCT

(10) International Publication Number WO 2005/039861 A2

(51) International Patent Classification7: A61F 5/448

B29C 65/00,

(74) Agent: INSPICOS A/S; Bøge Allé 5, P.O. Box 45,

(21) International Application Number:

PCT/DK2004/000728

(22) International Filing Date: 21 October 2004 (21.10.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

PA 2003 01571

24 October 2003 (24.10.2003)

(71) Applicant (for all designated States except US): COLO-PLAST A/S [DK/DK]; Holtedam 1, DK-3050 Humlebaek (DK).

(72) Inventors; and

(75) Inventors/Applicants (for US only): BAGER, Kim [DK/DK]; Chr. Winthersvej 36C, DK-2800 Lyngby (DK). FINK, Ingrid, Læsøe [DK/DK]; Pilebakken 2, DK-3540 Lynge (DK).


DK-2970 Hørsholm (DK).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


[Continued on next page]

(54) Title: AN OSTOMY MOUNTING WAFER AND A METHOD OF PREPARING IT



(57) Abstract: An ostomy body side mounting wafer and a method of preparing the ostomy body side mounting wafer, where the wafer is assembled from two parts using laser welding. The laser light is provided through one of the parts having a low or lower absorption of the laser light. The other part has a higher absorption of the laser light, whereby the interface between the two parts is heated at the welding zone(s) of the laser light. In this manner, an assembly is obtained independently of the thicknesses of the materials and even close to openings or other edges.





WO 2005/039861 A2



Published:

 without international search report and to be republished upon receipt of that report For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.